



SECTION 1: PRODUCT AND COMPANY INFORMATION

Product Name: X-Seal	Company Name: Marco Industries
Product Type: Expandable Foam	Contact Information: 9410 E 54 th St Tulsa, OK 74145
EMERGENCY CONTACT: Safety Advisor or 911	Ph. 918-622-4535
CHEMTREC: 1-800-424-9300	Fax 918-622-4536
DATE: 9-8-2010	

SECTION 2: COMPOSITION/INGREDIENT INFORMATION

COMPONENTS	%	ACGIH TLV	OSHA PEL	OTHER
Acrylic Impregnating Compound, water based dispersion	40-70			
Polyurethane Foam	30-60			
Acrylate Copolymer, Self-Adhesive	1-5			
TOTAL	100			

SECTION 3: PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT	n/a	SPECIFIC GRAVITY (H ₂ O=1)	1.1
VAPOR PRESSURE (mm Hg and Temp.)	n/a	MELTING POINT	n/a
VAPOR DENSITY (Air=1)	n/a	EVAPORATION RATE (Butyl Acetate=1)	n/a
SOLUBILITY IN WATER	n/a	WATER REACTIVE	n/a
FLASH POINT	n/a	DENSITY	n/a

APPEARANCE & ODOR: Tape appearance, gray in color, characteristic odor

SECTION 4: FIRE & EXPLOSION HAZARD DATA

FLASH POINT METHOD USED	n/a
AUTO-IGNITION TEMPERATURE	n/a
FLAMABILITY LIMITS IN AIR, % BY VOLUME	
LEL	n/a
UEL	n/a



SECTION 8: CONTROL & PROTECTIVE MEASURES

STEPS IF MATERIAL IS SPILLED or RELEASED	n/a
WASTE DISPOSAL	Waste not regulated under RCRA. Dispose of in compliance with state and local regulations
PRECAUTIONS IN HANDLING & STORAGE	n/a
OTHER PRECAUTIONS/HAZARDS	n/a

SECTION 9: DISCLAIMER

The data contained herein are furnished for information only and are believed to be reliable. However, Marco Industries, Inc does not assume responsibility for any results obtained by persons over whose methods Marco Industries, Inc has no control. It is the user's responsibility to determine the suitability of these products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Marco Industries, Inc products.