

The high performance underlayment choice with a 30 year limited warranty.

When you need a high strength light weight synthetic roof underlayment, HydraShell™ MAX is the choice for you. Manufactured from 100% synthetic materials, HydraShell™ MAX has a four layer construction making it 25 times stronger than #15 felt and 12 times stronger than #30 felt. It requires significantly few fasteners, and provides a tough, durable deck cover. The less weight per roll and the non-woven walking surface makes for a simple and easy installation. HydraShell™ MAX is designed for use under all types of roofing materials; including: asphalt shingles, synthetic shingles, cedar shakes, and metal, and is backed by a 30 year limited warranty.



Features and Benefits:

- Will not wrinkle or absorb water
- Remains Flexible in cold weather
- 100% synthetic
- 90 Day UV exposure rating
- Class A fire rating

- 25x stronger than #15 roofing felt
- 12x stronger than #30 roofing felt
- More coverage per roll
- Less weight per roll for easy installation
- Cool Gray surface to reduce heat build-up



| Physical Properties | HydraShell" MAX |
|------------------------|-----------------------|
| Roll Dimensions | 40" x 300' |
| Permeability | 0.1 perms |
| Water Transmission | Pass |
| Tear Strength | Md 33 lbs/CD 24 lbs |
| Tensile Strength | MD 95 lbs / CD 85 lbs |
| Burst Strength | 160 psi |
| Elongation | 20% |
| Weight per Square | 1.96 lbs |
| Nominal Thickness | 6.2 mils |
| Temp. Range (Internal) | -70 F to 240 F |



800.800.8590 / MarcoIndustries.com



Marco's Rapid Response™ delivers, faster and easier. Take advantage of free shipping with low minimum orders.