

# TILE OFF-RIDGE VENT

**A INNOVATIVE  
GOOSENECK VENT THAT IS  
DESIGNED WITH A HIGHER  
LIFT TO MAKE IT SUITABLE  
FOR TILE ROOFS**

*Lowest vent height  
in the market reduces  
curbside visibility*

*Mini louvers let attic  
air out while keeping  
water out from getting in*



*Completely enclosed  
front eliminates  
water infiltration*

## Marco's Tile Off-Ridge Vent is suitable for tile, synthetic, cedar, shake, and slate roofs.

The Tile Off-Ridge Vent contains perforated panel technology, which allows it to out perform other off-ridge vents in wind driven rain tests. It is guaranteed to have zero water entry at 110MPH wind-driven rain. Marco's Tile Off-Ridge Vent has a unique, completely enclosed design that, along with its low vent profile, helps reduce wind uplift and eliminates water infiltration.

- ▶ Innovative fully enclosed design
- ▶ Does not allow water infiltration
- ▶ No additional external baffle is needed in the front of the vent, saving time and money
- ▶ Made from durable 26-gauge galvaume steel
- ▶ Suitable for any pitch from 3/12 to 12/12
- ▶ 25 square inches of Net Free Venting Area per lineal foot and 100 square inches per 4 ft. unit
- ▶ Meets Energy Star color requirements
- ▶ Keeps insects and critters out
- ▶ High Quality & Durability - Reduces customer call-backs

## Attics need to breathe to keep cool and dry with proper ventilation.

- ▶ Reduces air conditioning maintenance costs
- ▶ Prevents wood rot which extends shingle and roof deck life
- ▶ Prevents mold and mildew
- ▶ Reduces utility costs



Roofing Ventilation & Accessories

The Marco  
Weather-Tite™  
System

Closure

Ventilation

Fasteners

Flashing

Sealants

Underlayment

Accessories

- Value drives everything we do. That's why we developed our Steep Slope Ventilation Division. This comprehensive line of products offer easy installation, remarkable building ventilation, lower utility costs, extended shingle and roof deck life, extreme durability, and outstanding warranties. Get more quality, more performance, and more value... Marco Industries.™

### Specs

**Net Free Area:** 25 sq. in. per Lineal ft

**Material:** 26 - Gauge Galvalume

**Codes & Standards:** FL Building Code

**Dimensions:** Width 23-1/2" x Height 6"

**Nominal Lengths:** 4'

**Color:** Black, Weatherwood, Mill

**Screws:** 1 3/4 Wood Type for Bottom Flange

**Roof Pitch:** Conforms to any pitch from 3/12 to 12/12

**Patents:** Pending

**Vent Hood:** Mini louvers in hood blocks water

**Interior Louver Panel:** Mini louvers in opposite direction to louvers on lower portion of hood as second water barrier

**Internal Baffle:** Placed at the top of the vent pan, the internal baffle is the third line of defense against water intrusion



Proudly Made in North America



### Easy Install

See our installation online at [marcoindustries.com](http://marcoindustries.com)

1. Space vent openings evenly across ridge. The opening size should be a minimum of a 2 1/2" by 46" cut between 2 sets of rafters. Note: Do not cut into rafters
2. If tiles have previously been installed on the roof, remove the tiles around sides and top of opening to provide space to install vent as per instructions.
3. Position vent over opening in deck.
4. Fasten side and top flanges securely with minimum 1 1/4" standard roofing nails. Space nails approximately 4" on the center and approximately 1 1/2" from outer edge of flange.
5. Seal flanges to sub roof membrane as per substrate manufacturer recommendations.
6. Cut tile to fit around vent and install per tile manufacturer recommendations.



Roofing Ventilation & Accessories

800.800.8590 / [MarcoIndustries.com](http://MarcoIndustries.com)



Marco's Rapid Response™ delivers, faster and easier. Take advantage of free shipping with low minimum orders.