


UNIVERSAL TILE RIDGE VENT

The perforated barrier and Weather-Tite nonwoven baffle create a multiple barrier system to keep out vermin, dust, debris, and wind-driven rain, while also allowing superior NFA.



Marco's Universal Tile Ridge Vent is an industry first, offering superior attic ventilation for homeowners and easy installation for you.

Made with rugged 26-gauge Galvalume steel, its durable design doesn't require a ridge board or separate brackets to install. The simple end-overlap unit feature prevents water infiltration at the seams. And a 40-year limited warranty offers peace of mind for decades to come.

- ▶ Fits any pitch from 3/12 to 12/12
- ▶ Keeps out leaks and wind-driven rain
- ▶ Provides 20 square inches of Net Free Venting Area per lineal foot and 80 square inches per unit
- ▶ Delivers optimal ventilation with installation at the ridge of the roof
- ▶ Offers pleasing aesthetics as it is concealed under the ridge cap
- ▶ TAS-100(a)-approved to meet the most stringent hurricane testing requirements
- ▶ Keeps out insects, critters, rain, snow, and debris with its advanced baffling system
- ▶ Reduces customer call-backs with quality build and durable design



Roofing Ventilation & Accessories

The Marco Weather-Tite™ System

Closure

Ventilation

Fasteners

Flashing

Sealants

Underlayment

Accessories

- Value drives everything we do. That's why we developed our Steep Slope Ventilation Division. This comprehensive line of products offer easy installation, remarkable building ventilation, lower utility costs, extended shingle and roof deck life, extreme durability, and outstanding warranties. Get more quality, more performance, and more value...Marco Industries™

Specs

Net Free Area: Over 20 sq. in. per Lineal ft, 80 sq. in per unit

Material: 26 - Gauge Galvalume and non-woven composite polyester

Nominal Lengths: 4'


Heights: 5" available

Codes & Standards: FL Building Code

Color: Mill

Roof Pitch: Conforms to any pitch from 3/12

Patents: Pending



Easy Install

Visit our website at MarcoIndustries.com for installation videos

1. Install tile roof components; roofing underlayment, battens (if used), and field tiles up to the row just below the ridge where the Universal Tile Ridge Vent will be installed. All components should be installed per the Tile Roof Institute installation manual observing specific regional climate requirements.
2. Using a chalk line, mark 1" on both sides of the ridge for truss construction (1" beyond ridge pole) as a guide for cutting a slot in the decking. The slot should be no closer than 12" to the end of the ridge.
3. Cut a 2" slot in the roof ridge on the bottom of the decking using a circular saw - avoid cutting trusses and rafters.
4. To ensure proper alignment along the ridge, run a chalk line down both sides of the ridge.
5. Center the Universal Tile Ridge Vent over the ridge slot. Use sealant recommended by the underlayment manufacturer between the vent flange and the roof deck. Place the first vent with the male end facing inwards. The vent flanges have a built in 6:12 pitch; for shallower roof pitches, simply press the vent downwards to flatten the flanges against the roof deck. For steeper pitches, press the vent body against the deck and bend the flanges against the deck while nailing in place.
6. Fasten the vent to the roof deck on approximately 12" centers using a nail gun, or hand nail using the existing pre-punched holes.
7. Apply a generous bead of Marco Weathertite™ Sealant along the circumference of the male end flange, including the deck flanges. Lower the female end of the next vent into place over the male end of the first vent, ensuring the sealant fills any gaps. Hold the vent down while nailing it into place. Repeat for all subsequent vents. Vents are self-centering to each other when sleeved together.
8. Cut the ridge anchor accessory to a length long enough so that it is flush with the edge of the roof. Place the ridge anchor adjacent to the Universal Tile Ridge Vent and seal with mastic and/or sealant. Fill end of ridge anchor with mortar to seal.
9. Install the cap tiles with mortar, adhesive, or fasteners.



Roofing Ventilation & Accessories

800.800.8590 / MarcoIndustries.com



Marco's Rapid Response™ delivers, faster and easier. Take advantage of free shipping with low minimum orders.