

# Tile Gooseneck Vent

## OUTSTANDING PERFORMANCE

The only Gooseneck Vent of its kind to pass the Standard TAS 100 Wind-Driven Rain Test



### Features:

- ▶ Quiet - no noisy damper opening and closing.
- ▶ Marco's Tile Gooseneck Vent is suitable for tile, synthetic, cedar, shake, and slate roofs.
- ▶ Promotes superior airflow and makes it ideal for kitchen or bathroom exhausts.
- ▶ Interior louver panel captures any moisture directing it to vent pan away from the attic.
- ▶ Suitable for any roof pitch from 3/12 to 12/12.
- ▶ Keeps insects and critters out.
- ▶ High Quality & Durability - Reduces customer call-backs.

 *Not to be Used as a Laundry Vent.*

## EXPAND YOUR ROOFING SYSTEM PERFORMANCE

**PREVENT LEAKS • PROTECT PROPERTY • ASSURE VENTILATION**

# INSTALLATION INSTRUCTIONS

## VALUE DRIVES EVERYTHING WE DO

Value drives everything we do. That's why we developed our Steep Slope Ventilation Division. This comprehensive line of products offer easy installation, remarkable building ventilation, lower utility costs, extended shingle and roof deck life, extreme durability, and outstanding warranties. Get more quality, more performance, and more value... Marco Industries™

## EASY INSTALL

See our installation online at [marcoindustries.com](http://marcoindustries.com)

- 1 Select required vent size; 4" Vent, 6" Vent, or 10" Vent
2. When installing vents on an existing tile roof: remove tiles immediately around sides and top of opening to provide space to install vent as per instructions below.
3. Position vent over opening in deck.
4. Fasten side and top flanges securely with minimum 1 1/4" standard roofing nails spaced 4" on center and 1 1/2" from outer edge of flange.
5. Seal flanges to sub-roof membrane as per substrate manufacturer recommendations.
6. Cut tile to fit around vent and install per tile manufacturer recommendations.



*High Profile*  
Tile Gooseneck Vent

*Low Profile*  
Tile Gooseneck Vent

### SPECS:

**Dimensions:** Width 19-3/16" x Height 10 1/4"

**Material:** 26 - gauge galvalume

**Codes & Standards:** FL Building Code, patents pending

**Roof Pitch:** Conforms to any pitch from 3/12" to 12/12"

**Color:** Galvalume and other colors available

**Sizes:** 4", 6" and 10"

**Vent Hood:** Mini louvers in lower portion of hood block water.

**Interior Louver Panel:** Acts as second water barrier.

**Internal Baffle:** Placed at the top of the vent pan, the internal baffle is the third line of defense against water intrusion.



 *Not to be Used as a Laundry Vent.*



1-800-800-8590 / [Marcoindustries.com](http://Marcoindustries.com)

 **MARCO**  
INDUSTRIES™  
Roofing Ventilation & Accessories